

2

AD-A236 053



INTATION PAGE

Form Approved
OPM No. 0704-0188

1 hour per response, including the time for reviewing instructions, searching existing data sources gathering and maintaining the data
g this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington
215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Information and Regulatory Affairs, Office of

1. AGENCY USE ONLY (Leave blank)

2. REPORT DATE

3. REPORT TYPE AND DATES COVERED

Final: 09 Sept 1990 to 03 Mar 1991

4. TITLE AND SUBTITLE

Meridian Software Systems, Inc., Meridian Ada, Version 4.1, Sun Microsystem 3/260
(Host & Target), 900909W1.11031

5. FUNDING NUMBERS

6. AUTHOR(S)

Wright-Patterson AFB, Dayton, OH
USA

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Ada Validation Facility, Language Control Facility ASD/SCEL
Bldg. 676, Rm 135
Wright-Patterson AFB
Dayton, OH 45433

8. PERFORMING ORGANIZATION
REPORT NUMBER

AVF-VSR-391.0491

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Ada Joint Program Office
United States Department of Defense
Pentagon, Rm 3E114
Washington, D.C. 20301-3081

10. SPONSORING/MONITORING AGENCY
REPORT NUMBER

11. SUPPLEMENTARY NOTES

DTIC
ELECTE
MAY 30 1991
S E D

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

Meridian Software Systems, Inc., Version 4.1, Wright-Patterson AFB, Sun Microsystems 3/260 SunOS, Version 4.1 (Host
& Target), ACVC 1.11.

14. SUBJECT TERMS

Ada programming language, Ada Compiler Val. Summary Report, Ada Compiler Val.
Capability, Val. Testing, Ada Val. Office, Ada Val. Facility, ANSI/MIL-STD-1815A, AJPO.

15. NUMBER OF PAGES

16. PRICE CODE

17. SECURITY CLASSIFICATION
OF REPORT
UNCLASSIFIED

18. SECURITY CLASSIFICATION
UNCLASSIFIED

19. SECURITY CLASSIFICATION
OF ABSTRACT
UNCLASSIFIED

20. LIMITATION OF ABSTRACT

Certificate Information

The following Ada implementation was tested and determined to pass ACVC 1.11. Testing was completed on 09 September 1990.

Compiler Name and Version: Meridian Ada, Version 4.1

Host Computer System: Sun Microsystems 3/260
SunOS, Version 4.1


Target Computer System: Sun Microsystems 3/260
SunOS, Version 4.1

Customer Agreement Number: 90-07-23-MSS

See section 3.1 for any additional information about the testing environment.


As a result of this validation effort, Validation Certificate 900909W1.11031 is awarded to Meridian Software Systems, Inc. This certificate expires on 1 March 1993.


This report has been reviewed and is approved.


Ada Validation Facility
Steven P. Wilson
Technical Director
ASD/SCEL
Wright-Patterson AFB OH 45433-6503



| | |
|--------------------|-------------------------------------|
| Accession For | |
| NTIS GRA&I | <input checked="" type="checkbox"/> |
| DTIC TAB | <input type="checkbox"/> |
| Unannounced | <input type="checkbox"/> |
| Justification | |
| By | |
| Distribution/ | |
| Availability Codes | |
| Dist | Avail and/or Special |
| A-1 | |


for Ada Validation Organization
Director, Computer & Software Engineering Division
Institute for Defense Analyses
Alexandria VA 22311


Ada Joint Program Office
Dr. John Solomond, Director
Department of Defense
Washington DC 20301

91 5 29 107

91-00771


AVF Control Number: AVF-VSR-391.0491
8 April 1991
90-07-23-MSS

Ada COMPILER
VALIDATION SUMMARY REPORT:
Certificate Number: 900909W1.11031
Meridian Software Systems, Inc.
Meridian Ada, Version 4.1
Sun Microsystems 3/260 => Sun Microsystems 3/260

Prepared By:
Ada Validation Facility
ASD/SCEL
Wright-Patterson AFB OH 45433-6503

Certificate Information

The following Ada implementation was tested and determined to pass ACVC 1.11. Testing was completed on 09 September 1990.

Compiler Name and Version: Meridian Ada, Version 4.1

Host Computer System: Sun Microsystems 3/260
SunOS, Version 4.1


Target Computer System: Sun Microsystems 3/260
SunOS, Version 4.1

Customer Agreement Number: 90-07-23-MSS


See section 3.1 for any additional information about the testing environment.

As a result of this validation effort, Validation Certificate 900909W1.11031 is awarded to Meridian Software Systems, Inc. This certificate expires on 1 March 1993.

This report has been reviewed and is approved.



Ada Validation Facility
Steven P. Wilson
Technical Director
ASD/SCEL
Wright-Patterson AFB OH 45433-6503



Ada Validation Organization
Director, Computer & Software Engineering Division
Institute for Defense Analyses
Alexandria VA 22311

Ada Joint Program Office
Dr. John Solomond, Director
Department of Defense
Washington DC 20301


DECLARATION OF CONFORMANCE

Customer: Meridian Software Systems, Inc.
Ada Validation Facility: ASD/SCEL, Wright-Patterson AFB OH 45433-6503
ACVC Version: 1.11
Ada Implementation:

Compiler Name and Version: Meridian Ada, Version 4.1
Host Computer System: Sun Microsystems 3/260
SunOS, Version 4.1
Target Computer System: Sun Microsystems 3/260
SunOS, Version 4.1

Customer's Declaration

I, the undersigned, representing Meridian Software Systems, Inc., declare that Meridian Software Systems, Inc. has no knowledge of deliberate deviations from the Ada Language Standard ANSI/MIL-STD-1815A in the implementation listed in this declaration. I declare that Meridian Software Systems, Inc. is the owner of the above implementation and the certificates shall be awarded in the name of the owner's corporate name.



Stowe Boyd, Vice President of Research and Development
Meridian Software Systems, Inc.
10 Pasteur Street
Irvine, CA 92718

Date: 3 August 1990

TABLE OF CONTENTS

| | | |
|------------|---|-----|
| CHAPTER 1 | INTRODUCTION | |
| 1.1 | USE OF THIS VALIDATION SUMMARY REPORT | 1-1 |
| 1.2 | REFERENCES | 1-2 |
| 1.3 | ACVC TEST CLASSES | 1-2 |
| 1.4 | DEFINITION OF TERMS | 1-3 |
| CHAPTER 2 | IMPLEMENTATION DEPENDENCIES | |
| 2.1 | WITHDRAWN TESTS | 2-1 |
| 2.2 | INAPPLICABLE TESTS | 2-1 |
| 2.3 | TEST MODIFICATIONS | 2-4 |
| CHAPTER 3 | PROCESSING INFORMATION | |
| 3.1 | TESTING ENVIRONMENT | 3-1 |
| 3.2 | SUMMARY OF TEST RESULTS | 3-1 |
| 3.3 | TEST EXECUTION | 3-2 |
| APPENDIX A | MACRO PARAMETERS | |
| APPENDIX B | COMPILATION SYSTEM OPTIONS | |
| APPENDIX C | APPENDIX F OF THE Ada STANDARD | |

CHAPTER 1

INTRODUCTION

The Ada implementation described above was tested according to the Ada Validation Procedures [Pro90] against the Ada Standard [Ada83] using the current Ada Compiler Validation Capability (ACVC). This Validation Summary Report (VSR) gives an account of the testing of this Ada implementation. For any technical terms used in this report, the reader is referred to [Pro90]. A detailed description of the ACVC may be found in the current ACVC User's Guide [UG89].

1.1 USE OF THIS VALIDATION SUMMARY REPORT

Consistent with the national laws of the originating country, the Ada Certification Body may make full and free public disclosure of this report. In the United States, this is provided in accordance with the "Freedom of Information Act" (5 U.S.C. #552). The results of this validation apply only to the computers, operating systems, and compiler versions identified in this report.

The organizations represented on the signature page of this report do not represent or warrant that all statements set forth in this report are accurate and complete, or that the subject implementation has no nonconformities to the Ada Standard other than those presented. Copies of this report are available to the public from the AVF which performed this validation or from:

National Technical Information Service
5285 Port Royal Road
Springfield VA 22161

Questions regarding this report or the validation test results should be directed to the AVF which performed this validation or to:

Ada Validation Organization
Institute for Defense Analyses
1801 North Beauregard Street
Alexandria VA 22311

INTRODUCTION

1.2 REFERENCES

- [Ada83] Reference Manual for the Ada Programming Language, ANSI/MIL-STD-1815A, February 1983 and ISO 8652-1987.
- [Pro90] Ada Compiler Validation Procedures, Version 2.1, Ada Joint Program Office, August 1990.
- [UG89] Ada Compiler Validation Capability User's Guide, 21 June 1989.

1.3 ACVC TEST CLASSES

Compliance of Ada implementations is tested by means of the ACVC. The ACVC contains a collection of test programs structured into six test classes: A, B, C, D, E, and L. The first letter of a test name identifies the class to which it belongs. Class A, C, D, and E tests are executable. Class B and class L tests are expected to produce errors at compile time and link time, respectively.

The executable tests are written in a self-checking manner and produce a PASSED, FAILED, or NOT APPLICABLE message indicating the result when they are executed. Three Ada library units, the packages REPORT and SPRT13, and the procedure CHECK_FILE are used for this purpose. The package REPORT also provides a set of identity functions used to defeat some compiler optimizations allowed by the Ada Standard that would circumvent a test objective. The package SPRT13 is used by many tests for Chapter 13 of the Ada Standard. The procedure CHECK_FILE is used to check the contents of text files written by some of the Class C tests for Chapter 14 of the Ada Standard. The operation of REPORT and CHECK_FILE is checked by a set of executable tests. If these units are not operating correctly, validation testing is discontinued.

Class B tests check that a compiler detects illegal language usage. Class B tests are not executable. Each test in this class is compiled and the resulting compilation listing is examined to verify that all violations of the Ada Standard are detected. Some of the class B tests contain legal Ada code which must not be flagged illegal by the compiler. This behavior is also verified.

Class L tests check that an Ada implementation correctly detects violation of the Ada Standard involving multiple, separately compiled units. Errors are expected at link time, and execution is attempted.

In some tests of the ACVC, certain macro strings have to be replaced by implementation-specific values -- for example, the largest integer. A list of the values used for this implementation is provided in Appendix A. In addition to these anticipated test modifications, additional changes may be required to remove unforeseen conflicts between the tests and implementation-dependent characteristics. The modifications required for this implementation are described in section 2.3.

INTRODUCTION

For each Ada implementation, a customized test suite is produced by the AVF. This customization consists of making the modifications described in the preceding paragraph, removing withdrawn tests (see section 2.1) and, possibly some inapplicable tests (see section 2.2 and [UG89]).

In order to pass an ACVC an Ada implementation must process each test of the customized test suite according to the Ada Standard.

1.4 DEFINITION OF TERMS

| | |
|---|---|
| Ada Compiler | The software and any needed hardware that have to be added to a given host and target computer system to allow transformation of Ada programs into executable form and execution thereof. |
| Ada Compiler Validation Capability (ACVC) | The means for testing compliance of Ada implementations, consisting of the test suite, the support programs, the ACVC user's guide and the template for the validation summary report. |
| Ada Implementation | An Ada compiler with its host computer system and its target computer system. |
| Ada Joint Program Office (AJPO) | The part of the certification body which provides policy and guidance for the Ada certification system. |
| Ada Validation Facility (AVF) | The part of the certification body which carries out the procedures required to establish the compliance of an Ada implementation. |
| Ada Validation Organization (AVO) | The part of the certification body that provides technical guidance for operations of the Ada certification system. |
| Compliance of an Ada Implementation | The ability of the implementation to pass an ACVC version. |
| Computer System | A functional unit, consisting of one or more computers and associated software, that uses common storage for all or part of a program and also for all or part of the data necessary for the execution of the program; executes user-written or user-designated programs; performs user-designated data manipulation, including arithmetic operations and logic operations; and that can execute programs that modify themselves during execution. A computer system may be a stand-alone unit or may consist of several inter-connected units. |

INTRODUCTION

| | |
|------------------------------|---|
| Conformity | Fulfillment by a product, process or service of all requirements specified. |
| Customer | An individual or corporate entity who enters into an agreement with an AVF which specifies the terms and conditions for AVF services (of any kind) to be performed. |
| Declaration of Conformance | A formal statement from a customer assuring that conformity is realized or attainable on the Ada implementation for which validation status is realized. |
| Host Computer System | A computer system where Ada source programs are transformed into executable form. |
| Inapplicable test | A test that contains one or more test objectives found to be irrelevant for the given Ada implementation. |
| ISO | International Organization for Standardization. |
| Operating System | Software that controls the execution of programs and that provides services such as resource allocation, scheduling, input/output control, and data management. Usually, operating systems are predominantly software, but partial or complete hardware implementations are possible. |
| Target Computer System | A computer system where the executable form of Ada programs are executed. |
| Validated Ada Compiler | The compiler of a validated Ada implementation. |
| Validated Ada Implementation | An Ada implementation that has been validated successfully either by AVF testing or by registration [Pro90]. |
| Validation | The process of checking the conformity of an Ada compiler to the Ada programming language and of issuing a certificate for this implementation. |
| Withdrawn test | A test found to be incorrect and not used in conformity testing. A test may be incorrect because it has an invalid test objective, fails to meet its test objective, or contains erroneous or illegal use of the Ada programming language. |

CHAPTER 2

IMPLEMENTATION DEPENDENCIES

2.1 WITHDRAWN TESTS

The following tests have been withdrawn by the AVO. The rationale for withdrawing each test is available from either the AVO or the AVF. The publication date for this list of withdrawn tests is 02 September 1990.

| | | | | | |
|---------|---------|---------|---------|---------|---------|
| E28005C | B28006C | C34006D | B41308B | C43004A | C45114A |
| C45346A | C45612B | C45651A | C46022A | B49008A | A74006A |
| B83022B | B83022H | B83025B | B83025D | B83026B | C83026A |
| C83041A | B85001L | C97116A | C98003B | BA2011A | CB7001A |
| CB7001B | CB7004A | CC1223A | BC1226A | CC1226B | BC3009B |
| BD1B02B | BD1B06A | AD1B08A | BD2A02A | CD2A21E | CD2A23E |
| CD2A32A | CD2A41A | CD2A41E | CD2A87A | CD2B15C | BD3006A |
| CD4022A | CD4022D | CD4024B | CD4024C | CD4024D | CD4031A |
| CD4051D | CD5111A | CD7004C | ED7005D | CD7005E | AD7006A |
| CD7006E | AD7201A | AD7201E | CD7204B | BD8002A | BD8004C |
| CD9005A | CD9005B | CDA201E | CE2107I | CE2119B | CE2205B |
| CE2405A | CE3111C | CE3118A | CE3411B | CE3412B | CE3812A |
| CE3814A | CE3902B | | | | |

2.2 INAPPLICABLE TESTS

A test is inapplicable if it contains test objectives which are irrelevant for a given Ada implementation. Reasons for a test's inapplicability may be supported by documents issued by ISO and the AJPO known as Ada Commentaries and commonly referenced in the format AI-ddddd. For this implementation, the following tests were determined to be inapplicable for the reasons indicated; references to Approved Ada Commentaries are included as appropriate.

IMPLEMENTATION DEPENDENCIES

The following 201 tests have floating-point type declarations requiring more digits than `SYSTEM.MAX_DIGITS`:

| | |
|-----------------------|-----------------------|
| C24113L..Y (14 tests) | C35705L..Y (14 tests) |
| C35706L..Y (14 tests) | C35707L..Y (14 tests) |
| C35708L..Y (14 tests) | C35802L..Z (15 tests) |
| C45241L..Y (14 tests) | C45321L..Y (14 tests) |
| C45421L..Y (14 tests) | C45521L..Z (15 tests) |
| C45524L..Z (15 tests) | C45621L..Z (15 tests) |
| C45641L..Y (14 tests) | C46012L..Z (15 tests) |

C35702A, C35713B, C45423B, B86001T, and C86006H check for the predefined type `SHORT_FLOAT`.

C35702B, C35713C, B86001U, and C86006G check for the predefined type `LONG_FLOAT`.

C35713D and B86001Z check for a predefined floating-point type with a name other than `FLOAT`, `LONG_FLOAT`, or `SHORT_FLOAT`.

A35801E checks that `FLOAT'FIRST..FLOAT'LAST` may be used as a range constraint in a floating-point type declaration; for this implementation that range exceeds the safe numbers and must be rejected. (See section 2.3)

C45423A, C45523A, and C45622A check that the proper exception is raised when operations results lie outside of the range of the base type if `MACHINE OVERFLOWS` is `TRUE` for various floating-point types; for this implementation, `MACHINE_OVERFLOWS` is `FALSE`.

C45531M..P (4 tests) and C45532M..P (4 tests) check fixed-point operations for types that require a `SYSTEM.MAX_MANTISSA` of 47 or greater.

C86001F recompiles package `SYSTEM`, making package `TEXT_IO`, and hence package `REPORT`, obsolete. For this implementation, the package `TEXT_IO` is dependent upon package `SYSTEM`.

B86001Y checks for a predefined fixed-point type other than `DURATION`.

CA2009C, CA2009F, BC3204C and BC3205D instantiate generic units before their bodies are compiled. This implementation creates a dependence on generic units as allowed by AI-00408 and AI-00530 such that the compilation of the generic unit bodies makes the instantiating units obsolete. (see section 2.3)

LA3004A..B (2 tests), EA3004C..D (2 tests), and CA3004E..F (2 tests) check for pragma `INLINE` for procedures and functions.

CD1009C uses a representation clause specifying a non-default size for a floating-point type.

IMPLEMENTATION DEPENDENCIES

CD2A84A, CD2A84E, CD2A84I..J (2 tests), and CD2A84O use representation clauses specifying non-default sizes for access types.

AE2101C and EE2201D..E (2 tests) use instantiations of package SEQUENTIAL_IO with unconstrained array types and record types with discriminants without defaults. These instantiations are rejected by this compiler.

AE2101H, EE2401D, and EE2401G use instantiations of package DIRECT_IO with unconstrained array types and record types with discriminants without defaults. These instantiations are rejected by this compiler.

The tests listed in the following table are not applicable because the given file operations are supported for the given combination of mode and file access method.

| Test | File Operation | Mode | File Access Method |
|---------|----------------|------------|--------------------|
| CE2102D | CREATE | IN FILE | SEQUENTIAL_IO |
| CE2102E | CREATE | OUT FILE | SEQUENTIAL_IO |
| CE2102F | CREATE | INOUT FILE | DIRECT_IO |
| CE2102I | CREATE | IN FILE | DIRECT_IO |
| CE2102J | CREATE | OUT FILE | DIRECT_IO |
| CE2102N | OPEN | IN FILE | SEQUENTIAL_IO |
| CE2102O | RESET | IN FILE | SEQUENTIAL_IO |
| CE2102P | OPEN | OUT FILE | SEQUENTIAL_IO |
| CE2102Q | RESET | OUT FILE | SEQUENTIAL_IO |
| CE2102R | OPEN | INOUT FILE | DIRECT_IO |
| CE2102S | RESET | INOUT FILE | DIRECT_IO |
| CE2102T | OPEN | IN FILE | DIRECT_IO |
| CE2102U | RESET | IN FILE | DIRECT_IO |
| CE2102V | OPEN | OUT FILE | DIRECT_IO |
| CE2102W | RESET | OUT FILE | DIRECT_IO |
| CE3102E | CREATE | IN FILE | TEXT_IO |
| CE3102F | RESET | Any Mode | TEXT_IO |
| CE3102G | DELETE | ----- | TEXT_IO |
| CE3102I | CREATE | OUT FILE | TEXT_IO |
| CE3102J | OPEN | IN FILE | TEXT_IO |
| CE3102K | OPEN | OUT FILE | TEXT_IO |

CE2107B..E (4 tests), CE2107L, CE2110B, and CE2111D attempt to associate multiple internal files with the same external file when one or more files is writing for sequential files.

CE2107G..H (2 tests), CE2110D, and CE2111H attempt to associate multiple internal files with the same external file when one or more files is writing for direct files. The proper exception is raised when multiple access is attempted.

IMPLEMENTATION DEPENDENCIES

CE2203A checks that WRITE raises USE_ERROR if the capacity of the external file is exceeded for SEQUENTIAL_IO. This implementation does not restrict file capacity.

CE2403A checks that WRITE raises USE_ERROR if the capacity of the external file is exceeded for DIRECT_IO. This implementation does not restrict file capacity.

CE3111B, CE3111D..E (2 tests), CE3114B, and CE3115A attempt to associate multiple internal files with the same external file when one or more files is writing for text files. The proper exception is raised when multiple access is attempted.

CE3304A checks that USE_ERROR is raised if a call to SET_LINE_LENGTH or SET_PAGE_LENGTH specifies a value that is inappropriate for the external file. This implementation does not have inappropriate values for either line length or page length.

CE3413B checks that PAGE raises LAYOUT_ERROR when the value of the page number exceeds COUNT'LAST. For this implementation, the value of COUNT'LAST is greater than 150000 making the checking of this objective impractical.

2.3 TEST MODIFICATIONS

Modifications (see section 1.3) were required for 9 tests.

The following tests were split into two or more tests because this implementation did not report the violations of the Ada Standard in the way expected by the original tests.

B22003A B83033B B85013D

A35801E was graded inapplicable by Evaluation Modification as directed by the AVO; the compiler rejects the use of the range FLOAT'FIRST..FLOAT'LAST as the range constraint of a floating-point type declaration because the bounds lie outside of the range of safe numbers (cf. ARM 3.5.7 (12)).

CA2009C, CA2009F, BC3204C, and BC3205D were graded inapplicable by Evaluation Modification as directed by the AVO. Because this implementation makes the units with instantiations obsolete (see section 2.2), the Class C tests were rejected at link time and the Class B tests were compiled without error.

EA1003B was processed with the option "-fI" so that code would be generated for all of the legal units of this test file. Without this option, the entire compilation would have been rejected due to errors within only some of the units (which is also an acceptable result).

CHAPTER 3

PROCESSING INFORMATION

3.1 TESTING ENVIRONMENT

The Ada implementation tested in this validation effort is described adequately by the information given in the initial pages of this report.

For a point of contact for technical information about this Ada implementation system, see:

Technical Support
10 Pasteur Street
Irvine, California 92718
(714) 727 - 0700

For a point of contact for sales information about this Ada implementation system, see:

Jim Smith
10 Pasteur Street
Irvine, California 92718
(714) 727 - 0700

Testing of this Ada implementation was conducted at the customer's site by a validation team from the AVF.

3.2 SUMMARY OF TEST RESULTS

An Ada Implementation passes a given ACVC version if it processes each test of the customized test suite in accordance with the Ada Programming Language Standard, whether the test is applicable or inapplicable; otherwise, the Ada Implementation fails the ACVC [Pro90].

PROCESSING INFORMATION

For all processed tests (inapplicable and applicable), a result was obtained that conforms to the Ada Programming Language Standard.

| | |
|---|------|
| Total Number of Applicable Tests | 3807 |
| Total Number of Withdrawn Tests | 74 |
| Processed Inapplicable Tests | 88 |
| Non-Processed I/O Tests | 0 |
| Non-Processed Floating-Point Precision Tests | 201 |
| Total Number of Inapplicable Tests | 289 |
| Total Number of Tests for ACVC 1.11 | 4170 |

All I/O tests of the test suite were processed because this implementation supports a file system. The above number of floating-point tests were not processed because they used floating-point precision exceeding that supported by the implementation. When this compiler was tested, the tests listed in section 2.1 had been withdrawn because of test errors.

3.3 TEST EXECUTION

Version 1.11 of the ACVC comprises 4170 tests. When this compiler was tested, the tests listed in section 2.1 had been withdrawn because of test errors. The AVF determined that 289 tests were inapplicable to this implementation. All inapplicable tests were processed during validation testing except for 201 executable tests that use floating-point precision exceeding that supported by the implementation. In addition, the modified tests mentioned in section 2.3 were also processed.

A magnetic tape containing the customized test suite (see section 1.3) was taken on-site by the validation team for processing. The contents of the magnetic tape was loaded directly onto the host computer.

After the test files were loaded onto the host computer, the full set of tests was processed by the Ada implementation.

Testing was performed using command scripts provided by the customer and reviewed by the validation team. See Appendix B for a complete listing of the processing options for this implementation. It also indicates the default options. The options invoked explicitly for validation testing during this test were:

PROCESSING INFORMATION

| Switch | Effect |
|--------|---|
| -fE | Generate error file for the Ada listing utility (alu). |
| -fI | Ignore compilation errors and continue generating code for legal units within the same compilation file (for test EA1003B). |
| -fQ | Suppresses "added to library" and "Generating code for" information messages. |
| -fw | Suppresses informative warning messages. |
| -c | Produce continuous form Ada listings (no page headers). |
| -p | Obey PRAGMA PAGE directives within program even through the -c flag says not to generate page breaks. |
| -s | Output Ada listing to the standard output file instead of to a disk file. |

Test output, compiler and linker listings, and job logs were captured on magnetic tape and archived at the AVF. The listings examined on-site by the validation team were also archived.

APPENDIX A MACRO PARAMETERS

This appendix contains the macro parameters used for customizing the ACVC. The meaning and purpose of these parameters are explained in [UG89]. The parameter values are presented in two tables. The first table lists the values that are defined in terms of the maximum input-line length, which is the value for \$MAX_IN_LEN--also listed here. These values are expressed here as Ada string aggregates, where "V" represents the maximum input-line length.

| Macro Parameter | Macro Value |
|------------------------------|--|
| \$BIG_ID1 | (1..V-1 => 'A', V => '1') |
| \$BIG_ID2 | (1..V-1 => 'A', V => '2') |
| \$BIG_ID3 | (1..V/2 => 'A') & '3' & (1..V-1-V/2 => 'A') |
| \$BIG_ID4 | (1..V/2 => 'A') & '4' & (1..V-1-V/2 => 'A') |
| \$BIG_INT_LIT | (1..V-3 => '0') & "298" |
| \$BIG_REAL_LIT | (1..V-5 => '0') & "690.0" |
| \$BIG_STRING1 | '"' & (1..V/2 => 'A') & '"' |
| \$BIG_STRING2 | '"' & (1..V-1-V/2 => 'A') & '1' & '"' |
| \$BLANKS | (1..V-20 => ' ') |
| \$MAX_LEN_INT_BASED_LITERAL | "2:" & (1..V-5 => '0') & "11:" |
| \$MAX_LEN_REAL_BASED_LITERAL | "16:" & (1..V-7 => '0') & "F.E:" |
| \$MAX_STRING_LITERAL | '"' & (1..V-2 => 'A') & '"' |

MACRO PARAMETERS

The following table lists all of the other macro parameters and their respective values.

| Macro Parameter | Macro Value |
|-----------------------------------|---------------------------------|
| \$MAX_IN_LEN | 200 |
| \$ACC_SIZE | 32 |
| \$ALIGNMENT | 2 |
| \$COUNT_LAST | 2147483646 |
| \$DEFAULT_MEM_SIZE | 1024 |
| \$DEFAULT_STOR_UNIT | 8 |
| \$DEFAULT_SYS_NAME | M68000 |
| \$DELTA_DOC | 2.0**(-31) |
| \$ENTRY_ADDRESS | 16#0# |
| \$ENTRY_ADDRESS1 | 16#1# |
| \$ENTRY_ADDRESS2 | 16#2# |
| \$FIELD_LAST | 2147483647 |
| \$FILE_TERMINATOR | ' ' |
| \$FIXED_NAME | NO_SUCH_FIXED_TYPE |
| \$FLOAT_NAME | NO_SUCH_FLOAT_TYPE |
| \$FORM_STRING | "" |
| \$FORM_STRING2 | "CANNOT RESTRICT_FILE_CAPACITY" |
| \$GREATER_THAN_DURATION | 90000.0 |
| \$GREATER_THAN_DURATION BASE LAST | 10000000.0 |
| \$GREATER_THAN_FLOAT_BASE_LAST | 1.8E+308 |
| \$GREATER_THAN_FLOAT_SAFE_LARGE | 1.0E308 |

MACRO PARAMETERS

\$GREATER_THAN_SHORT_FLOAT_SAFE_LARGE
 1.0E308

 \$HIGH_PRIORITY 20

 \$ILLEGAL_EXTERNAL_FILE_NAME1
 7NODIRECTORY/FILENAME1

 \$ILLEGAL_EXTERNAL_FILE_NAME2
 7NODIRECTORY/FILENAME2

 \$INAPPROPRIATE_LINE_LENGTH
 -1

 \$INAPPROPRIATE_PAGE_LENGTH
 -1

 \$INCLUDE_PRAGMA1 PRAGMA INCLUDE ("A28006D1.ADA")
 \$INCLUDE_PRAGMA2 PRAGMA INCLUDE ("B28006F1.ADA")

 \$INTEGER_FIRST -2147483648
 \$INTEGER_LAST 2147493647
 \$INTEGER_LAST_PLUS_1 2147483648

 \$INTERFACE_LANGUAGE C

 \$LESS_THAN_DURATION -90000.0
 \$LESS_THAN_DURATION_BASE_FIRST
 -10000000.0

 \$LINE_TERMINATOR ASCII.LF

 \$LOW_PRIORITY 1

 \$MACHINE_CODE_STATEMENT
 INSTRUCTION' (VAL=>16#4E71#);

 \$MACHINE_CODE_TYPE INSTRUCTION

 \$MANTISSA_DOC 31

 \$MAX_DIGITS 15

 \$MAX_INT 2147483647
 \$MAX_INT_PLUS_1 2147483648

 \$MIN_INT -2147483648

MACRO PARAMETERS

| | |
|-----------------------|--|
| \$NAME | BYTE_INTEGER |
| \$NAME_LIST | M68000 |
| \$NAME_SPECIFICATION1 | /s/acvc/X2120A |
| \$NAME_SPECIFICATION2 | /s/acvc/X2120B |
| \$NAME_SPECIFICATION3 | /s/acvc/X3119A |
| \$NEG_BASED_INT | 16#FFFFFFFE# |
| \$NEW_MEM_SIZE | 1024 |
| \$NEW_STOR_UNIT | 8 |
| \$NEW_SYS_NAME | M68000 |
| \$PAGE_TERMINATOR | ASCII.LF & ASCII.FF |
| \$RECORD_DEFINITION | RECORD VAL: SHORT_INTEGER; END RECORD; |
| \$RECORD_NAME | INSTRUCTION |
| \$TASK_SIZE | 32 |
| \$TASK_STORAGE_SIZE | 2048 |
| \$TICK | 1.0 |
| \$VARIABLE_ADDRESS | FCNDECL.VAR_ADDRESS |
| \$VARIABLE_ADDRESS1 | FCNDECL.VAR_ADDRESS1 |
| \$VARIABLE_ADDRESS2 | FCNDECL.VAR_ADDRESS2 |
| \$YOUR_PRAGMA | NO_SUCH_PRAGMA |

APPENDIX B

COMPILATION SYSTEM OPTIONS

The compiler options of this Ada implementation, as described in this Appendix, are provided by the customer. Unless specifically noted otherwise, references in this appendix are to compiler documentation and not to this report.

MERIDIAN ADA COMPILER OPTIONS

- fD Generate debugging output. The -fD option causes the compiler to generate the appropriate code and data for operation with the Meridian Ada Debugger.
- fe Annotate assembly language listing. The -fe option causes the compiler to annotate an assembly language output file. The output is supplemented by comments containing the Ada source statements corresponding to the assembly language code sections written by the code generator. To use this option, the -S option must also be specified, otherwise the annotated file is not emitted.
- fE Generate error log file. The -fE option causes the compiler to generate a log file containing all the error messages and warning messages produced during compilation. The error log file has the same name as the source file, with the extension .err. For example, the error log file for simple.adb is simple.err. The error log file is placed in the current working directory. In the absence of the -fE option, the error log information is sent to the standard output stream.
- fI Ignore compilation errors and continue generating code for legal units within the same compilation file.
- fL Generate exception location information. The -fL option causes location information (source file names and line numbers) to be maintained for internal checks. This

COMPILATION SYSTEM OPTIONS

information is useful for debugging in the event that an "Exception never handled" message appears when an exception propagates out of the main program. This flag causes the code to be somewhat larger. If -fL is not used, exceptions that propagate out of the main program will behave in the same way, but no location information will be printed with the "Exception never handled" message.

- fN Suppress numeric checking. The -fN flag suppresses two kinds of numeric checks for the entire compilation: division check and overflow check. These checks are described in section 11.7 of the LRM. This flag reduces the size of the code.
- fQ Suppress "added to library" and "Generating code for" information messages normally output by the compiler.
- fs Suppress all checks. The -fs flag suppresses all automatic checking, including numeric checking. This flag is equivalent to using pragma suppress on all checks. This flag reduces the size of the code, and is good for producing "production quality" code or for benchmarking the compiler. Note that there is a related ada option, -fN to suppress only certain kinds of numeric checks.
- fU Inhibit library update. The -fU option inhibits library updates. This is of use in conjunction with the -S option. Certain restrictions apply to use of this option.
- fv Compile verbosely. The compiler prints the name of each subprogram, package, or generic as it is compiled. Information about the symbol table space remaining following compilation of the named entity is also printed in the form "[nK]".
- fw Suppress warning messages. With this option, the compiler does not print warning messages about ignored pragmas, exceptions that are certain to be raised at run-time, or other potential problems that the compiler is otherwise forbidden to deem as errors by the LRM.
- g The -g option instructs the compiler to run an additional optimization pass. The optimizer removes common sub-expressions, dead code and unnecessary jumps. It also does loop optimizations.
- K Keep internal form file. This option is used in conjunction with the Optimizer. Without this option, the compiler deletes internal form files following code generation.

COMPILATION SYSTEM OPTIONS

-lmodifiers

Generate listing file. The -l option causes the compiler to create a listing. Optional modifiers can be given to affect the listing format. You can use none or any combination of the following modifiers:

- c Use continuous listing format. The listing by default contains a header on each page. Specifying -lc suppresses both pagination and header output, producing a continuous listing.
- p Obey pragma page directives. Specifying -lp is only meaningful if -lc has also been given. Normally -lc suppresses all pagination, whereas -lcp suppresses all pagination except where explicitly called for within the source file with a pragma page directive.
- s Use standard output. The listing by default is written to a file with the same name as the source file and the extension .lst, as in simple.lst from simple.adb. Specifying -ls causes the listing file to be written to the standard output stream instead.
- t Generate relevant text output only. The listing by default contains the entire source program as well as interspersed error messages and warning messages. Specifying -lt causes the compiler to list only the source lines to which error messages or warning messages apply, followed by the messages themselves.

The default listing file generated has the same name as the source file, with the extension .lst. For example, the default listing file produced for simple.adb has the name simple.lst. The listing file is placed in the current working directory. Note: -l also causes an error log file to be produced, as with the -fE option.

-L library-name

Default: ada.lib

Use alternate library. The -L option specifies an alternative name for the program library.

- N No compile. This option causes the ada command to do a "dry run" of the compilation process. The command invoked for each processing step is printed. This is similar to the -P option, but no actual processing is performed.

COMPILATION SYSTEM OPTIONS

- P Print compile. This option causes the ada command to print out the command invoked for each processing step as it is performed.
- S Produce assembly code. This option causes the code generator to produce an assembly language source file and to halt further processing.

LINKER OPTIONS

The linker options of this Ada implementation, as described in this Appendix, are provided by the customer. Unless specifically noted otherwise, references in this appendix are to linker documentation and not to this report.

MERIDIAN ADA LINKER OPTIONS

- A Aggressively inline. This option instructs the optimizer to aggressively inline subprograms when used in addition to the -G option. Typically, this means that subprograms that are only called once are inlined. If only the -G option is used, only subprograms for which pragma inline has been specified are inlined.

-c compiler-program-name

Default: (as stored in program library)

Use alternate compiler. The -c option specifies the complete (non relative) directory path to the Meridian Ada compiler. This option overrides the compiler program name stored in the program library. The -c option is intended for use in cross-compiler configurations, although under such circumstances, an appropriate library configuration is normally used instead.

- f Suppress main program generation step. The -f option suppresses the creation and additional code generation steps for the temporary main program file. The -f option can be used when a simple change has been made to the body of a compilation unit. If unit elaboration order is changed, if the specification of a unit is changed, or if new units are added, then this option should not be used.

- F Use library routines with on line (MC68881) code. If

COMPILATION SYSTEM OPTIONS

you use this option, the MC68881 or MC68882 co-processor must reside on the machine on which you run the program.

- g Perform global optimization only. The -g option causes bamp to invoke the global optimizer on your program. Compilation units to be optimized globally must have been compiled with the ada -K option.
- G Perform global and local optimization. The -G option causes bamp to perform both global and local optimization on your program. This includes performing pragma inline. As with the -g option, compilation units to be optimized must have been compiled with the ada -K option.
- I Link the program with a version of the tasking run-time which supports pre-emptive task scheduling. This option produces code which handles interrupts more quickly, but has a slight negative impact on performance in general.

-L library-name

Default: ada.lib

Use alternate library. The -L option specifies the name of the program library to be consulted by the bamp program. This option overrides the default library name.

- n No link. The -n option suppresses actual object file linkage, but creates and performs code generation on the main program file.
- N No operations. The -N option causes the bamp command to do a "dry run"; it prints out the actions it takes to generate the executable program, but does not actually perform those actions. The same kind of information is printed by the -P option.

-o output-file-name

Default: file

Use alternate executable file output name. The -o option specifies the name of the executable program file written by the bamp command. This option overrides the default output file name.

- P Print operations. The -P option causes the bamp command to print out the actions it takes to generate the executable program as the actions are performed.
- S Use switchable library routines. Use this option if you don't know if you have a co-processor or a co-processor

COMPILATION SYSTEM OPTIONS

is not needed.

- v Link verbosely. The -v option causes the bamp command to print out information about what actions it takes in building the main program.
- W Suppress warnings. This option allows you to suppress warnings from the optimizer.

APPENDIX C

APPENDIX F OF THE Ada STANDARD

The only allowed implementation dependencies correspond to implementation-dependent pragmas, to certain machine-dependent conventions as mentioned in Chapter 13 of the Ada Standard, and to certain allowed restrictions on representation clauses. The implementation-dependent characteristics of this Ada implementation, as described in this Appendix, are provided by the customer. Unless specifically noted otherwise, references in this Appendix are to compiler documentation and not to this report. Implementation-specific portions of the package STANDARD, which are not a part of Appendix F, are:

package STANDARD is

...

type INTEGER IS RANGE -2_147_483_648 .. 2_147_483_647;

type FLOAT is digits 15
range -1.79769313486231E+308 .. 1.79769313486231E+308;

type DURATION is delta 0.0001 range -86400.0 .. 86400.0;

type LONG_INTEGER is range -2_147_483_648 .. 2_147_483_647;

type SHORT_INTEGER is range -32768 .. 32767;

type BYTE_INTEGER is range -128 .. 127;

...

end STANDARD;

Appendix F Implementation-Dependent Characteristics

This appendix lists implementation-dependent characteristics of Meridian Ada. Note that there are no preceding appendices. This appendix is called *Appendix F* in order to comply with the Reference Manual for the Ada Programming Language* (LRM) ANSI/MIL-STD-1815A which states that this appendix be named Appendix F.

Implemented Chapter 13 features include length clauses, enumeration representation clauses, record representation clauses, address clauses, interrupts, package **system**, machine code insertions, pragma **interface**, and unchecked programming.

F.1 Pragmas

The implemented pre-defined pragmas are:

| | |
|------------------|---|
| elaborate | See the LRM section 10.5. |
| interface | See section F.1.1. |
| list | See the LRM Appendix B. |
| pack | See section F.1.2. |
| page | See the LRM Appendix B. |
| priority | See the LRM Appendix B. |
| suppress | See section F.1.3. |
| inline | See the LRM section 6.3.2. This pragma is not actually effective unless you compile/link your program using the global optimizer. |

The remaining pre-defined pragmas are accepted, but presently ignored:

| | | |
|--------------------|---------------------|--------------------|
| controlled | optimize | system_name |
| shared | storage_unit | |
| memory_size | | |

Named parameter notation for pragmas is not supported.

When illegal parameter forms are encountered at compile time, the compiler issues a warning message rather than an error, as required by the Ada language definition. Refer to the LRM Appendix B for additional information about the pre-defined pragmas.

F.1.1 Pragma Interface

The form of pragma **interface** in Meridian Ada is:

```
pragma interface ( language, subprogram [, "link-name" ] );
```

where:

| | |
|-------------------|---|
| <i>language</i> | is the interface language, one of the names assembly , builtin , c , or internal . The names builtin and internal are reserved for use by Meridian compiler maintainers in run-time support packages. |
| <i>subprogram</i> | is the name of a subprogram to which the pragma interface applies. |
| <i>link-name</i> | is an optional string literal specifying the name of the non-Ada subprogram corresponding to the Ada subprogram named in the second parameter. If <i>link-name</i> is omitted, then <i>link-</i> |

*All future references to the Reference Manual for the Ada Programming Language appear as the LRM.

name defaults to the value of *subprogram translated to lowercase*. Depending on the language specified, some automatic modifications may be made to the *link-name* to produce the actual object code symbol name that is generated whenever references are made to the corresponding Ada subprogram.

It is appropriate to use the optional *link-name* parameter to **pragma interface** only when the interface subprogram has a name that does not correspond at all to its Ada identifier or when the interface subprogram name cannot be given using rules for constructing Ada identifiers (e.g. if the name contains a '\$' character).

The characteristics of object code symbols generated for each interface language are:

| | |
|-----------------|---|
| assembly | The object code symbol is the same as <i>link-name</i> . |
| builtin | The object code symbol is the same as <i>link-name</i> , but prefixed with two underscore characters ("__"). This language interface is reserved for special interfaces defined by Meridian Software Systems, Inc. The builtin interface is presently used to declare certain low-level run-time operations whose names must not conflict with programmer-defined or language system defined names. |
| c | The object code symbol is the same as <i>link-name</i> , but with one underscore character ('_') prepended. This is the convention used by the C compiler. |
| internal | No object code symbol is generated for an internal language interface; this language interface is reserved for special interfaces defined by Meridian Software Systems, Inc. The internal interface is presently used to declare certain machine-level bit operations. |

No automatic data conversions are performed on parameters of any interface subprograms. It is up to the programmer to ensure that calling conventions match and that any necessary data conversions take place when calling interface subprograms.

A **pragma interface** may appear within the same declarative part as the subprogram to which the **pragma interface** applies, following the subprogram declaration, and prior to the first use of the subprogram. A **pragma interface** that applies to a subprogram declared in a package specification must occur within the same package specification as the subprogram declaration; the **pragma interface** may not appear in the package body in this case. A **pragma interface** declaration for either a private or nonprivate subprogram declaration may appear in the private part of a package specification.

Pragma interface for library units is not supported.

Refer to the LRM section 13.9 for additional information about **pragma interface**.

F.1.2 Pragma Pack

Pragma pack is implemented for composite types (records and arrays).

Pragma pack is permitted following the composite type declaration to which it applies, provided that the pragma occurs within the same declarative part as the composite type declaration, before any objects or components of the composite type are declared.

Note that the declarative part restriction means that the type declaration and accompanying **pragma pack** cannot be split across a package specification and body.

The effect of **pragma pack** is to minimize storage consumption by discrete component types whose ranges permit packing. Use of **pragma pack** does not defeat allocations of alignment storage gaps for some record types. **Pragma pack** does not affect the representations of real types, pre-defined integer types, and access types.

F.1.3 Pragma Suppress

Pragma suppress is implemented as described in the LRM section 11.7, with these differences:

- Presently, `division_check` and `overflow_check` must be suppressed via a compiler flag. `-fn : pragma suppress` is ignored for these two numeric checks.
- The optional "`ON =>`" parameter name notation for `pragma suppress` is ignored.
- The optional second parameter to `pragma suppress` is ignored: the pragma always applies to the entire scope in which it appears.

F.2 Attributes

All attributes described in the LRM Appendix A are supported.

F.3 Standard Types

Additional standard types are defined in Meridian Ada:

- `byte_integer`
- `short_integer`
- `long_integer`

The standard numeric types are defined as:

```

type byte_integer is range -128 .. 127;
type short_integer is range -32768 .. 32767;
type integer      is range -2147483648 .. 2147483647;
type long_integer is range -2147483648 .. 2147483647;
type float is digits 15
  range -1.79769313486231E+308 .. 1.79769313486231E+308;
type duration is delta 0.0001 range -86400.0000 .. 86400.0000;
```

F.4 Package System

The specification of package system is:

```

package system is
  type address is new integer;
  type name is (m68000);
  system_name : constant name := m68000;
  storage_unit : constant := 8;
  memory_size : constant := 1024;
  -- System-Dependent Named Numbers
  min_int : constant := -2147483648;
  max_int : constant := 2147483647;
  max_digits : constant := 15;
  max_mantissa : constant := 31;
  fine_delta : constant := 2.0 ** (-31);
  tick : constant := 1.0;
  -- Other System-Dependent Declarations
```

subtype priority is integer range 1 .. 20;

The value of **system.memory_size** is presently meaningless.

F.5 Restrictions on Representation Clauses

F.5.1 Length Clauses

A size specification (**t' size**) is rejected if fewer bits are specified than can accommodate the type. The minimum size of a composite type may be subject to application of **pragma pack**. It is permitted to specify precise sizes for unsigned integer ranges, e.g. 8 for the range 0 .. 255. However, because of requirements imposed by the Ada language definition, a full 32-bit range of unsigned values, i.e. 0 .. (2**32) - 1, cannot be defined, even using a size specification.

The specification of collection size (**t' storage_size**) is evaluated at run-time when the scope of the type to which the length clause applies is entered, and is therefore subject to rejection (via **storage_error**) based on available storage at the time the allocation is made. A collection may include storage used for run-time administration of the collection, and therefore should not be expected to accommodate a specific number of objects. Furthermore, certain classes of objects such as unconstrained discriminant array components of records may be allocated outside a given collection, so a collection may accommodate more objects than might be expected.

The specification of storage for a task activation (**t' storage_size**) is evaluated at run-time when a task to which the length clause applies is activated, and is therefore subject to rejection (via **storage_error**) based on available storage at the time the allocation is made. Storage reserved for a task activation is separate from storage needed for any collections defined within a task body.

The specification of small for a fixed point type (**t' small**) is subject only to restrictions defined in the LRM section 13.2.

F.5.2 Enumeration Representation Clauses

The internal code for the literal of an enumeration type named in an enumeration representation clause must be in the range of **standard.integer**.

The value of an internal code may be obtained by applying an appropriate instantiation of **unchecked_conversion** to an integer type.

F.5.3 Record Representation Clauses

The storage unit offset (the **at static_simple_expression** part) is given in terms of 8-bit storage units and must be even.

A bit position (the **range** part) applied to a discrete type component may be in the range 0 .. 15, with 0 being the least significant bit of a component. A range specification may not specify a size smaller than can accommodate the component. A range specification for a component not accommodating bit packing may have a higher upper bound as appropriate (e.g. 0 .. 31 for a discriminant **string** component). Refer to the internal data representation of a given component in determining the component size and assigning offsets.

Components of discrete types for which bit positions are specified may not straddle 16-bit word boundaries.

The value of an alignment clause (the optional **at mod** part) must evaluate to 1, 2, 4, or 8, and may not be smaller than the highest alignment required by any component of the record.

F.5.4 Address Clauses

An address clause may be supplied for an object (whether constant or variable) or a task entry, but not for a subprogram, package, or task unit. The meaning of an address clause supplied for a task entry is given in section F.5.5.

An address expression for an object is a 32-bit segmented memory address of type **system.address**.

F.5.5 Interrupts

A task entry's address clause can be used to associate the entry with a UNIX signal. Values in the range 0 . . 31 are meaningful, and represent the signals corresponding to those values.

An interrupt entry may not have any parameters.

F.5.6 Change of Representation

There are no restrictions for changes of representation effected by means of type conversion.

F.6 Implementation-Dependent Components

No names are generated by the implementation to denote implementation-dependent components.

F.7 Unchecked Conversions

There are no restrictions on the use of **unchecked_conversion**. Conversions between objects whose sizes do not conform may result in storage areas with undefined values.

F.8 Input-Output Packages

A summary of the implementation-dependent input-output characteristics is:

- In calls to **open** and **create**, the *form* parameter must be the empty string (the default value).
- More than one internal file can be associated with a single external file for reading only. For writing, only one internal file may be associated with an external file; Do not use **reset** to get around this rule.
- Temporary sequential and direct files are given names. Temporary files are deleted when they are closed.
- File I/O is buffered; text files associated with terminal devices are line-buffered.
- The packages **sequential_io** and **direct_io** cannot be instantiated with unconstrained composite types or record types with discriminants without defaults.

F.9 Source Line and Identifier Lengths

Source lines and identifiers in Ada source programs are presently limited to 200 characters in length.